



# CS Plus<sup>350SS</sup>

## High volume, self-cooled induction cap sealing system

The CS Plus<sup>350SS</sup> brings the most advanced, patented self-cooled cap sealing technology to high volume lines, *with the ability to handle high line speeds.*

Completely water-free and fan-free, the self-contained CS Plus<sup>350SS</sup> offers the ultimate in reliability and performance.

Whatever your conveyor speed, the CS Plus<sup>350SS</sup> integrates easily into your line. It is shipped ready to roll up to your conveyor and begin sealing caps from 5 to 120mm. The easy-to-use controls permit a variety of settings including an "Energy Saver Mode" and "Motion Sensing." To learn more or to place an order, contact us today at [800-231-6008](tel:800-231-6008), or [sales@lepel.com](mailto:sales@lepel.com).

### BENEFITS OF CAP SEALING

Tamper evident

---

Leakproof

---

Longer shelf life

---

Reduced pilferage

---

Enhanced customer confidence

---

# CS Plus<sup>350SS</sup>

## FEATURES

- **Advanced, self-contained, convection cooled system:** operates in high ambient temperature and humidity conditions
- **Smooth, precise adjustment of sealing head height**
- **Easy-to-operate, legible microprocessor controls:** allow user-defined parameters such as Percent Power and Energy Save



- **System integrity monitoring:** for power, current, frequency, phase, temperature and communication
- **Remote capability:** allows a second control panel to be located away from the sealing head
- **Solid state design with high-efficiency sealing heads**
- **Stainless steel, NEMA 4X enclosure and modular components**
- **Motion Sensing package:** to monitor line speed, stalls, alignment and tolerance setting
- **Optional 3-phase Power Supply**

## SPECIFICATIONS

Input	230 V <sub>AC</sub> 14 Amps Max 50/60 Hz 1 phase (optional 3 phase)
Cap Size	5 to 120mm
Weight	300 lbs.
Crated Weight	350 lbs.
Height	Max 88" with light tower
Height Under Sealing Head	Min 40" Max 60"
Footprint	32" x 32"

## BENEFITS

- **Water-free:** requires no water system or plumbing
- **Fan-free sealing head:** eliminates filter changes and downtime
- **No moving parts:** eliminates maintenance and cleaning
- **Quicker setup with no assembly:** just uncrate and roll it up to your line

## ACCESSORIES

- **Interface panel (1):** permits use of accessories such as remote control panel with five remote inputs and three relay outputs
- **Light tower (2):** alerts operators of status, with three color indicators (green, yellow and red) and audible alarm
- **Remote control panel**
- **E-Stop:** emergency stop button



**LEPEL**

An Inductotherm Group Company

### LepeL Corporation

W227 N937 Westmound Drive • Waukesha, WI 53186  
Telephone: 800-231-6008 • Fax: 262-782-3299