



Experienced People. Efficient Solutions.



CS Plus^{200SS}

An enhanced self-cooled induction cap sealer

The CS Plus^{200SS} builds on the ingenuity of Lepel's patented self-cooled technology to provide outstanding sealing performance. The CS Plus^{200SS} is shipped fully assembled and is *ready to roll up to your line to begin sealing.*

With no sealing head fan and no water cooling system, the CS Plus^{200SS} offers superior reliability and operation.

The cost-efficient CS Plus^{200SS} accommodates most line speed requirements across a broad range of industries, sealing 5 to 120mm caps at moderate to high line speeds. Its easy-to-use controls allow users to enter a variety of settings. To learn more or to place an order, contact us today at **800-231-6008**, or sales@cap-sealing.com.

BENEFITS OF CAP SEALING

Tamper evident

Leakproof

Longer shelf life

Reduced pilferage

Enhanced customer confidence

CS Plus^{200SS}

FEATURES

- **Advanced, self-contained, convection cooled system:** operates in high ambient temperature and humidity conditions
- **Easy-to-operate, legible microprocessor controls:** allow user-defined parameters such as Percent Power and Energy Save



- **Smooth, precise adjustment of sealing head height**
- **System integrity monitoring:** for power, current, frequency, phase, temperature and communication
- **Remote capability:** allows a second control panel to be located away from the sealing head
- **Solid state design with high-efficiency sealing heads**
- **Stainless steel, NEMA 4X enclosure and modular components**
- **Optional Motion Sensing package:** to monitor line speed, stalls, alignment and tolerance setting

SPECIFICATIONS

Input	230 V _{AC} 10 Amps Max 50/60 Hz 1 phase
Line Speed	Moderate to high
Cap Size	5 to 120mm
Weight	300 lbs.
Crated Weight	350 lbs.
Height	Max 88" with light tower
Height under Sealing Head	Min 40" Max 60"
Footprint	32" x 32"

BENEFITS

- **Water-free:** requires no water system or plumbing
- **Fan-free sealing head:** eliminates filter changes and downtime
- **No maintenance or cleaning**
- **Quicker setup with no assembly:** just uncrate, roll it up to your line and plug it in

ACCESSORIES

- **Interface panel (1):** permits use of accessories such as remote control panel with five remote inputs and three relay outputs
- **Light tower (2):** alerts operators of status, with three color indicators (green, yellow and red) and audible alarm
- **Remote control panel**
- **E-Stop:** emergency stop button



Lepel

Lepel Cap Sealing
730 Larry Ct. • Waukesha, WI 53186
Phone: 262-782-0450 • Fax: 262-782-3299

Lepel Corporation
200 G Executive Dr. • Edgewood, NY 11717
Phone: 631-586-3300 • Fax: 631-586-3232