



CS Plus Jr. H2C

Hand-to-Conveyor Cap Sealing System

The CS Plus Jr H2C offers the most versatile, cost-effective induction cap sealing for applications ranging from single caps to low volume conveyor lines.

The power supply features a simple, multi-function LCD display. In addition, it automatically detects and adjusts for the sealing head that is attached, making it extremely easy to go from using one of four available hand-held sealing head options to using the conveyor sealing head on the stand.

The CS Plus Jr H2C delivers strong, tamper-evident seals that prevent leakage and ensure integrity for a wide range of products, including food, pharmaceuticals, beverages, cosmetics, solvents, petroleum products and chemicals. To learn more or to place an order, contact us at [800-231-6008](tel:800-231-6008) or sales@cap-sealing.com today.

BENEFITS OF CAP SEALING

Tamper evident

Leakproof

Longer shelf life

Reduced pilferage

Enhanced customer
confidence

CS Plus Jr. H2C

FEATURES

- **Solid state design with high-efficiency sealing head**
- **Stainless steel, NEMA 4X sealing head**
- **Versatile Connectivity:** connects to the Energy Unit via a standard 6 ft. (183 cm) cable (optional extension up to 15 ft.) with a 10-pin connector
- **Coil Auto-Detection Capability:** Energy Unit recognizes in-line as well as hand-held sealing heads, automatically limiting output power to each coil



- **Heat On light (green color):** informs the operator when the sealing head is energized
- **Easy Height Adjustment:** the sealing head can be installed on either a customer-supplied fixture or a LEPEL-manufactured Stationary Stand with a convenient hand crank
- **Optimized Output Design:** the sealing head can seal foil sizes from 28–100mm — without skewing — at conveyor speeds from 20–45 ft./minute, depending on the size, material, and cap construction, etc.

SPECIFICATIONS

Input Voltage	95–245 V AC 50/60 Cycle
Phase	1
Power Rating	1kW at 110 V AC 1.2kW at 220 V AC
Ambient Temperature Range	32–97°F (0–36°C)
In-Line Head:	
Length	20.25" (51.4 cm)
Width	12.5" (31.7 cm) <i>including heat sink</i>
Height	5" (12.7 cm)
Weight	44.25 lb. (20.1 kg)
Stationary Stand:	
Weight	80 lb. (39.29 kg)
Adjustable from floor to bottom of sealing head	Min 34" (86.4 cm) Max 54" (13.72 cm)

BENEFITS

- **Increased production**
- **Reduced cost of upgrading**
- **Water-free:** requires no water system or plumbing
- **No maintenance or cleaning**
- **Smooth, precise adjustment of sealing head height**

ACCESSORIES

- **Hand-Held Sealing Heads:** Four hand-held sealing head options are available:
 - Small for caps from 5mm to 58mm
 - Large for caps from 20mm to 83mm
 - Extra large for caps from 20mm to 120mm
 - Special for Yorker, sport caps, etc. from 5mm to 38mm



Lepel

Lepel Cap Sealing
730 Larry Ct. • Waukesha, WI 53186
Phone: 262-782-0450 • Fax: 262-782-3299

Lepel Corporation
200 G Executive Dr. • Edgewood, NY 11717
Phone: 631-586-3300 • Fax: 631-586-3232